centro ricerche-sviluppo e laboratori prove
settori legno-arredo, ambiente e alimenti

CATAS S.p.A.
Iscr. Reg. Imprese Udine
nr. iscr. C.F. 01818850305
Reg. Impr. UD 20663
P. IVA : 01818850305
C.Soc. € 1.003.650,00 i.v.

Sede: Via Antica, 24/3
33048 S. Giovanni al Nat. UD
Tel. 0432.747211 r.a.
Fax 0432.747250
http://www.catas.com
lab@catas.com

Filiale:
Via Braille, 5
20851 Lissone MB
Tel. 039.464567
Fax 039.464565
lissone@catas.com

Date received: 10/09/15

Date of issue: 12/11/15

Report consists of 1 test report.

Defects before testing: None

Sample name: K-PUSH TECH EMBEDEED 37 WITH MAGNET NORMAL SPRING

FERRAMENTA LIVENZA S.R.L.
VIALE L. ZANUSSI 21
33070 MARON DI BRUGNERA (PN)
ITALIA

SAMPLE N° 201220

List performed tests:

1. Durability of pivoted doors ISO 7170:2005, clause 7.1.4



This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.

centro ricerche-sviluppo e laboratori prove
settori legno-arredo, ambiente e alimenti

CATAS S.p.A.
Iscr. Reg. Imprese Udine
nr. iscr. C.F. 01818850305
Reg. Impr. UD 20663
P. IVA : 01818850305
C.Soc. € 1.003.650,00 i.v.

Sede: Via Antica, 24/3
33048 S. Giovanni al Nat. UD
Tel. 0432.747211 r.a.
Fax 0432.747250
http://www.catas.com
lab@catas.com

Filiale:
Via Braille, 5
20851 Lissone MB
Tel. 039.464567
Fax 039.464565
lissone@catas.com

TEST REPORT

201220 / 1

Date received: 10/09/15
Date of test: 04/11/15
Date of issue: 12/11/15



FERRAMENTA LIVENZA S.R.L.
VIALE L. ZANUSSI 21
33070 MARON DI BRUGNERA (PN)
ITALIA

Sample name: K-PUSH TECH EMBEDEED 37 WITH MAGNET NORMAL SPRING

Durability of pivoted doors ISO 7170:2005, clause 7.1.4

Type of door: two hinges pivoted door

Dimensions: 595 x 20 x 770 (height) mm

Material: wood based panel

Application point: in correspondence of the push to open device

Tests results:

Load on door kg	Number of cycles	Remarks
2	80000	No defects

Note: number of cycles as customer specifications.

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.